New product

- Very small, neat linear LED system
- Interior or exterior use (IP20 or IP67 versions)
- White or warm white LEDs or choice of colours
- Cove or cornice lighting
- Display lighting

A very small linear LED system, which will suit dozens of different applications. The low profile is an aluminium alloy extrusion, the IP20 interior version having a frosted cover, whilst the IP67 exterior unit is resin filled and has a clear appearance. Each length comes with clips for fixing or the extrusion can be bonded to suitable surfaces.





CLC section



CLC with mounting clip

CLC Module

Material	Aluminium alloy
Finish	Clear anodised
LED	350mA CREE
Cable Length	3 metres
Power Supply	See page 59
Options	Clear (IP67) or frosted cover (IP20)

Module lengths - number of LEDs

Length	CLC Single colour
230	2
630	6
830	8

CLC [XXX] [XX] [XX]

- **RE** - resin filled, exterior **UP** - unfilled, interior
- **W**-white **WW**-warm white **B**-blue*
- **230** - 230mm long **630** - 630mm long **830** - 830mm long

Example: **CLC230BRE** is a CL Cove with red LEDs, 230mm long, resin filled for IP67 protection
*Other colours are available to special order: Red, Green and Amber.

For drivers, connectors and control options see page 59.
For typical wiring arrangements see page 61.